

# LynxNet StrobelLED

SKU #950-LYNX-ST-P-1



The Lynx-ST-P-1 indoor strobe is a PoE network device that has visual and audible alerts. Alerts are activated by the LynxGuide server. Alerts can be activated until an all clear is sent or a preset timer expires. Power can be PoE. Configuration is easy with the 12 VDC programming power supply (one per order) and a direct ethernet connection to a PC. Once configured the LynxNet StrobelLED can operate on an optional 12 VDC power supply or the built in PoE module.



## Features and Benefits

- Strobe choices: red, blue, amber, or green with programmable audible tone
- Can be activated by any Lynx alert
- Supervised by the LynxGuide server

### GENERAL SPECIFICATIONS:

**Width:** 5.2"

**Length:** 7.65"

**Height:** 4.45"

**Weight:** 2.4 Lbs.

**Power:** DC Power or PoE

**PS Input Voltage:** 100-240 VAC

**PS Output Voltage:** 12 VDC, 1.0 amp

**POE:** Class 2, 5.5 Watts Max

**Supervision Interval:** Default 5 Minutes

**Communication Protocol:** The LynxNet hardware and Lynx Client software achieves bidirectional communication through a client-initiated, persistent socket session to the LynxGuide server on ports 10117-10121. No network ingress connections are required. All server communications are TLS encrypted. In addition to providing security, this method is ideal if the hardware is behind a gateway, as no NAT rules are required to achieve connectivity.